CYNTEK
www.cyntek.es

CX520Z

WALK-BEHIND FLOOR SCRUBBER



PROFESSIONAL PERFORMANCE, FLAWLESS RESULTS

The **CX520Z** combines robustness, durability and an optimized design to deliver efficient, reliable cleaning on all types of surfaces. Its 3–4 mm thick stainless-steel chassis, with double-layer anti-corrosion primer and powder coating, provides exceptional resistance to corrosion and impacts, extending the machine's service life even in the most demanding environments.

- STAINLESS STEEL CHASSIS
- HIGH DURABILITY
- EFFICIENT CLEANING
- HIGH PERFORMANCE



Scrubbing head
520 mm working width with one 500 mm diameter brush.



Control handles
Intuitive and ergonomic. With accelerator.



U-shaped squeegee
830 mm. Aluminium body with silicone blades.



Battery compartment
Easy access for quick, safe maintenance.



LED lighting
High-intensity front light.



Vacuum system
With stainless-steel filter and automatic float shut-off.

TECHNICAL SPECIFICATIONS

ELECTRICAL SYSTEM

Operating voltage:	24 Volts
Battery type:	2 x 12 V / 100 Ah AGM
Runtime:	Up to 4 hours
Charger:	External

BRUSHES

Scrubbing width:	520 mm
Max. theoretical productivity:	2,600 m²/h
Number of brushes:	1
Brush diameter:	500 mm
Head adjustment:	Automatic
Head pressure:	20 kg
Brush motor:	2 x 24 V / 550 W

TANKS

Solution:	65 litres (stainless steel filter)
Recovery:	75 litres

VACUUM SYSTEM

Vacuum motor:	24 V / 500 W (2 stages)
Filter:	Stainless steel mesh

SQUEEGEE

Body:	830 mm - Aluminium - U-shaped
Blades:	Silicone (tool-free replacement)

TRACTION

System:	Brushless rear-wheel drive
Control:	Push handle with accelerator
Travel:	Forward (5 km/h) / Reverse
Max. gradient:	16°
Traction motor:	24 V / 500 W

BRAKES

Service brake:	Electronic and mechanical
Parking brake:	Electronic and mechanical

CHASSIS

STAINLESS STEEL (3–4 mm thick)

DIMENSIONS

Length/Width/Height (mm):	1,300 x 830 x 1,010
Weight without batteries:	135 kg

ADDITIONAL FEATURES

Noise:	67 dB(A)

Battery indicator
Low-battery protection
Electronic water-level sensor
Anti-corrosion primer
Emergency stop switch

EUROPEAN CERTIFICATION (CE)

AVAILABLE EXCLUSIVELY AT: