CYNTEK
www.cyntek.es

# CX680Z

## WALK-BEHIND FLOOR SCRUBBER




## SUPERIOR PERFORMANCE FOR LARGE AREAS

The CX680Z combines durability, power and efficiency for fast, effective cleaning of large areas in professional environments. Its dual-brush system and wide scrubbing path help maximize productivity and reduce working time, while its stainless-steel chassis provides excellent strength and durability, even in demanding environments.

STAINLESS STEEL CHASSIS | HIGH DURABILITY | EFFICIENT CLEANING | HIGH PERFORMANCE



**Dual scrubbing brushes**
680 mm working width with 2 brushes, 340 mm diameter.



**Control handle**
Intuitive and ergonomic. With physical buttons.



**U-shaped squeegee**
1,200 mm. Aluminium body with silicone blades.



**Battery compartment**
Easy access for quick, safe maintenance.



**LED lighting**
High-intensity front light.



**Vacuum system**
Stainless-steel filter with automatic float shut-off.

## TECHNICAL SPECIFICATIONS

### ELECTRICAL SYSTEM
- Operating voltage: 24 Volts
- Battery type: 2 x 12 V / 100 Ah AGM
- Runtime: Up to 3 hours
- Charger: External

### BRUSHES
- Scrubbing width: 680 mm
- Max. theoretical productivity: 3,400 m²/h
- Number of brushes: 2
- Brush diameter: 340 mm
- Head adjustment: Manual
- Head pressure: 30 kg
- Brush motor: 2 x 24 V / 380 W

### TANKS
- Solution tank: 65 litres (stainless steel filter)
- Recovery tank: 75 litres

### VACUUM SYSTEM
- Vacuum motor: 24 V / 500 W (2 stages)
- Filter: Stainless steel mesh

### SQUEEGEE
- Body: 830 mm - Aluminium - U-shaped
- Blades: Silicone (tool-free replacement)

### TRACTION
- System: Brushless rear-wheel drive
- Control: Steering wheel and accelerator pedal
- Travel: Forward (5 km/h) / Reverse
- Max. gradient: 16°
- Traction motor: 24 V / 500 W

### BRAKES
- Service brake: Electronic and mechanical
- Parking brake: Electronic and mechanical

### CHASSIS
**STAINLESS STEEL** (3–4 mm thick)

### DIMENSIONS
- Length/Width/Height (mm): 1,300 x 830 x 1,010
- Weight without batteries: 155 kg

### ADDITIONAL FEATURES
- Noise: 67 dB(A)
- Battery indicator
- Low-battery protection
- Electronic water-level sensor
- Anti-corrosion primer
- Emergency stop switch

**EUROPEAN CERTIFICATION (CE)**

## AVAILABLE EXCLUSIVELY AT: