CYNTEK
www.cyntek.es

CX700

RIDE-ON FLOOR SCRUBBER



DESIGNED FOR CLEANING LARGE AREAS

The **CX700** is designed to deliver high cleaning performance across large areas, combining power, capacity and ease of operation. Its dual brushes and productivity of up to 4,900 m²/h ensure efficient cleaning in less time, while its large-capacity tanks and robust stainless-steel chassis provide excellent durability for intensive work.

STAINLESS STEEL CHASSIS | **HIGH DURABILITY** | **EFFICIENT CLEANING** | **HIGH PERFORMANCE**



Dual scrubbing brushes
700 mm working width with 2 brushes, 340 mm diameter.



Steering wheel
Intuitive and ergonomic. With physical buttons.



U-shaped squeegee
1,030 mm. Aluminium body with silicone blades.



Battery compartment
Easy access for quick, safe maintenance.



LED lighting
High-intensity front light.



Vacuum system
With stainless-steel filter and automatic shut-off by float.

TECHNICAL SPECIFICATIONS

ELECTRICAL SYSTEM

Operating voltage:	24 Volts
Battery type:	2 x 12 V / 103 Ah AGM
Runtime:	Up to 3 hours
Charger:	External

BRUSHES

Scrubbing width:	700 mm
Theoretical max. productivity:	4,900 m²/h
Number of brushes:	2
Brush diameter:	340 mm
Head adjustment:	Manual
Brush pressure:	30 kg
Brush motor:	2 x 24 V / 380 W

TANKS

Solution:	70 litres (stainless steel filter)
Recovery:	90 litres

VACUUM SYSTEM

Vacuum motor:	24 V / 500 W (2 stages)
Filter:	Stainless steel mesh

SQUEEGEE

Body:	1,030 mm – Aluminium – U-shaped
Blades:	Silicone (tool-free replacement)

TRACTION

System:	Brushless rear-wheel drive
Control:	Steering wheel and accelerator pedal
Travel:	Forward (6 km/h) / Reverse
Max. gradient:	16°
Traction motor:	24 V / 500 W

BRAKES

Service brake:	Electronic and mechanical
Parking brake:	Electronic and mechanical

CHASSIS

STAINLESS STEEL (4–5 mm thick)

DIMENSIONS

Length/Width/Height (mm):	1,460 x 1,030 x 1,110
Weight without batteries:	225 kg

ADDITIONAL FEATURES

Noise:	67 dB(A)

Battery indicator
Low-battery protection
Electronic water-level sensor
Anti-corrosion primer
Emergency stop switch

EUROPEAN CERTIFICATION (CE)

AVAILABLE EXCLUSIVELY AT: