CYNTEK
www.cyntek.es

CX800

RIDE-ON FLOOR SCRUBBER



MORE POWER, MORE CLEANING
MORE PERFORMANCE

The CX800 is designed to deliver maximum productivity when cleaning large areas, combining power, runtime and robustness. Its dual brushes and output of up to 5,320 m²/h ensure efficient cleaning in less time, while its large-capacity tanks and stainless-steel chassis provide excellent resistance and durability in the most demanding working environments.

STAINLESS STEEL CHASSIS | **HIGH DURABILITY** | **EFFICIENT CLEANING** | **HIGH PERFORMANCE**



Dual scrubbing brushes
760 mm working width with 2 brushes, 380 mm diameter.



Steering wheel
Intuitive and ergonomic. With physical buttons.



U-shaped squeegee
1,120 mm. Aluminium body with silicone blades.



Battery compartment
Easy access for quick, safe maintenance.



LED lighting
High-intensity front light.



Vacuum system
Stainless steel filter and automatic shut-off by float.

TECHNICAL SPECIFICATIONS

ELECTRICAL SYSTEM
- Operating voltage: 24 Volts
- Battery type: 3 x 8 V / 153 Ah
- Runtime: Up to 4 hours
- Charger: External

BRUSHES
- Scrubbing width: 760 mm
- Theoretical max. productivity: 5,320 m²/h
- Number of brushes: 2
- Brush diameter: 380 mm
- Head adjustment: Automatic
- Brush pressure: 35 kg
- Brush motor: 2 x 24 V / 380 W

TANKS
- Solution: 90 litres (stainless steel filter)
- Recovery: 100 litres

VACUUM SYSTEM
- Vacuum motor: 24 V / 500 W (2 stages)
- Filter: Stainless steel mesh

SQUEEGEE
- Body: 1,120 mm - Aluminium - U-shaped
- Blades: Silicone (tool-free replacement)

TRACTION
- System: Brushless rear-wheel drive
- Control: Steering wheel and accelerator pedal
- Travel: Forward (6 km/h) / Reverse
- Max. gradient: 16°
- Traction motor: 24 V / 500 W

BRAKES
- Service brake: Electronic and mechanical
- Parking brake: Electronic and mechanical

CHASSIS
STAINLESS STEEL (4–5 mm thick)

DIMENSIONS
- Length/Width/Height (mm): 1,630 x 1,130 x 1,280
- Weight without batteries: 265 kg

ADDITIONAL FEATURES
- Noise: 67 dB(A)
- Battery indicator
- Low-battery protection
- Electronic water-level sensor
- Anti-corrosion primer
- Emergency stop switch

EUROPEAN CERTIFICATION (CE)

AVAILABLE EXCLUSIVELY AT: