CYNTEK
www.cyntek.es

CX900
RIDE-ON FLOOR SCRUBBER



PROFESSIONAL EFFICIENCY, FLAWLESS RESULTS

The **CX900** stands out for its robust design, stability and ease of operation, delivering comfortable and efficient cleaning. Its durable construction, high-performance scrubbing and drying systems, and long runtime make it an ideal solution for maintaining large areas to impeccable standards, reducing working time and delivering professional results in the most demanding conditions.

- **STAINLESS STEEL CHASSIS**
- **HIGH DURABILITY**
- **EFFICIENT CLEANING**
- **HIGH PERFORMANCE**



Dual scrubbing brushes
900 mm working width with 2 brushes, 450 mm diameter.



Steering wheel
Intuitive and ergonomic. With physical buttons.



U-shaped squeegee
1,200 mm. Aluminium body with silicone blades.



Battery compartment
Easy access for quick, safe maintenance.



DUAL LED LIGHTING
High-intensity front lighting.



Vacuum system
Stainless steel filter and automatic shut-off by float.

TECHNICAL SPECIFICATIONS

ELECTRICAL SYSTEM
- Operating voltage: 24 Voltts
- Battery type: 4 x 6 V / 203 Ah
- Runtime: Up to 4 hours
- Charger: External

BRUSHES
- Scrubbing width: 900 mm
- Theoretical max. productivity: 8,100 m²/h
- Number of brushes: 2
- Brush diameter: 450 mm
- Head adjustment: Automatic
- Brush pressure: 45 kg
- Brush motor: 2 x 24 V / 550 W

TANKS
- Solution: 150 litres (stainless steel filter)
- Recovery: 160 litres

VACUUM SYSTEM
- Vacuum motor: 24 V / 600W (3 stages)
- Filter: Stainless steel mesh

SQUEEGEE
- Body: 1,200 mm – Aluminium – U-shaped
- Blades: Silicone (tool-free replacement)

TRACTION
- System: Brushless rear-wheel drive
- Control: Push handle with accelerator
- Travel: Forward (9 km/h) / Reverse
- Max. gradient: 16°
- Traction motor: 24 V / 1,200 W

BRAKES
- Service brake: Electronic and mechanical
- Parking brake: Electronic and mechanical

CHASSIS
STAINLESS STEEL (4–6 mm thick)

DIMENSIONS
- Length/Width/Height (mm): 1,660 x 1,250 x 1,380
- Weight without batteries: 370 kg

ADDITIONAL FEATURES
- Noise: 67 dB(A)
- Battery indicator
- Low-battery protection
- Electronic water-level sensor
- Anti-corrosion primer
- Emergency stop switch

EUROPEAN CERTIFICATION (CE)

AVAILABLE EXCLUSIVELY AT: